

iWave AIR PURIFIERS



PATHOGEN TEST RESULTS

All tests were run using proprietary NPBI™ technology.

SARS-CoV-2 (Covid-19)

TIME IN CHAMBER

30 MINUTES

RATE OF REDUCTION

99.4%

INNOVATIVE
BIoANALYSIS

This test was run using the iWave-C (GPS-DM48-AC) in a test designed to mimic ionization conditions like that of a commercial aircraft's fuselage.

Based on viral titrations, it was determined that at 10 minutes, 84.2% of the virus was inactivated. At 15 minutes, 92.6% of the virus was inactivated, and at 30 minutes, 99.4% of the virus was inactivated.

Human Coronavirus 229E

TIME IN CHAMBER

60 MINUTES

RATE OF REDUCTION


90%

ALG
ANALYTICAL
LAB GROUP

This test was run in a test chamber in a lab setting with the Nu-Calgon iWave-R Air Purifier P/N 4900-20.

A petri dish containing a pathogen is placed underneath a laboratory hood, then monitored to assess the pathogen's reactivity to Needle Point Bi-polar Ionization (NPBI) over time. This controlled environment allows for comparison across different types of pathogens.

iWave's Needle Point Bi-polar Ionization (NPBI) technology is used in a wide range of applications across diverse environmental conditions. Since locations will vary, clients should evaluate their individual application and environmental conditions when making an assessment regarding the technology's potential benefits.

 Nu-Calgon